

Park Lantern BOLARD M 4,0





DETAILED DESCRIPTION



PRODUCT DESCRIPTION

The modern simple form of the luminaire is built with an aluminum body, attached to the foundation. The upper part is an optical chamber with an LED source and a frosted PMMA diffuser, which eliminates glare. Designed for: illumination of public spaces, parks, etc.

HEIGHT: 4 m

TECHNICAL SPECIFICATIONS


Voltage	230 V
Source power / fixture	Recommended: integrated 45 W/5400 lm
Lifetime	70.000 h LB 80/20
Optics	S
Ambient temperature	-30 ÷ +45
Light color	4000 3000 *
Ingress Protection	IP65
Protection class	I II *
CE	Yes

^{*}choice

MECHANICAL DATA

Foundation	FBK-90/18	
Column/body material	Aluminium	
Lampshade	PMMA	
Metal color		White 9003
		Grey 7043
		Graphite 7016
		Black 9005
	RAL*	

ON ORDER



^{**}on special order

INDEX	NAZWA NAME	WYMIARY / DIMENSIONS (cm)		ŹRÓDŁO ŚWIATŁA / SOURCE OF LIGHT		OPRAWA / FIXTURE			FUNDAMENT	
		H/h,/h₂	D	W	lm	Im / W	W	lm	Im / W	FOUNDATION
190-1111-400029	BOLARD M LP 4,0	400/360	-/13,3	41,5	6500	155	45	5400	120	FBK-90/18

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.

