





**ELMARCO**  
GOOD FORM FOR LIGHTING

ELMARCO Technika Świetlna Sp. z o.o. Sp. K.  
Ul. Krzemowa 7, 81-577 Gdynia,  
tel. (58) 552 84 27

## Park Lantern BOLARD R 3,0



### OPTICS



„S”



### DETAILED DESCRIPTION

| INDEX           | NAZWA<br>NAME   | WYMIARY / DIMENSIONS (cm) |        | ŹRÓDŁO ŚWIATŁA / SOURCE OF LIGHT |      |        | OPRAWA / FIXTURE |      |        | FUNDAMENT<br>FOUNDATION |
|-----------------|-----------------|---------------------------|--------|----------------------------------|------|--------|------------------|------|--------|-------------------------|
|                 |                 | H/h <sub>1</sub>          | D      | W                                | lm   | lm / W | W                | lm   | lm / W |                         |
| 190-1111-300014 | BOLARD R LP 3,0 | 300/260                   | -/13,3 | 41,5                             | 6500 | 155    | 45               | 5400 | 120    | FBK-90/18               |

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.



### PRODUCT DESCRIPTION

Modern, simple form of the fixture made of an aluminum body, fixed to the foundation. The upper part is an optical chamber with a LED source. Diffuser made of transparent PMMA. Applied rasters eliminate glare and provide proper light distribution.

Designed for: illumination of public spaces, parks, etc.

HEIGHT: 3 m

### TECHNICAL SPECIFICATIONS


|                        |                                      |
|------------------------|--------------------------------------|
| Voltage                | 230 V                                |
| Source power / fixture | Recommended: Integrated 45 W/5400 lm |
| Lifetime               | 70.000 h LB 80/20                    |
| Optics                 | <b>S</b>                             |
| Ambient temperature    | -30 ÷ +45                            |
| Light color            | 4000 3000 *                          |
| Ingress Protection     | <b>IP65</b>                          |
| Protection class       | <b>I II</b> *                        |
| CE                     | Yes                                  |

\* choice

### MECHANICAL DATA

|                      |  |
|----------------------|--|
| Foundation           | FBK-90/18  |
| Column/body material | Aluminium  |
| Lampshade            | PMMA   |
| Metal color          | <div>White 9003</div> <div>Grey 7043</div> <div>Graphite 7016</div> <div>Black 9005</div> <div><b>RAL*</b></div> |

### ON ORDER



\*\* on special order