




## Garden Lamp BOLUX 1,2



### PRODUCT DESCRIPTION

Cylindrical aluminum column with a characteristic oblique undercut allows to fix the LED light source at an angle illuminating paths or create other accents in gardens, public spaces.

HEIGHT: 1,2 m

### TECHNICAL SPECIFICATIONS


Voltage	230 V
Source power / fixture	Recommended: Integrated 8,5 W/1050 lm
Lifetime	70.000 h LB 80/20
Ambient temperature	-30 ÷ +45
Light color	<input type="checkbox"/> 4000 <input type="checkbox"/> 3000 *
Ingress Protection	<b>IP65</b>
Protection class	<input type="checkbox"/> I <input type="checkbox"/> II *
CE	Yes

\* choice

### MECHANICAL DATA

Foundation	FBO-50/7,5
Column/body material	Aluminium
Lampshade	-
Metal color	<input type="checkbox"/> White 9003 <input type="checkbox"/> Grey 7043 <input type="checkbox"/> Graphite 7016 <input type="checkbox"/> Black 9005 <input type="checkbox"/> <b>RAL*</b>

### ON ORDER



\*\* on special order

### DETAILED DESCRIPTION

INDEX	NAZWA NAME	WYMIARY / DIMENSIONS (cm)		ŹRÓDŁO ŚWIATEŁA / SOURCE OF LIGHT			OPRAWA / FIXTURE			FUNDAMENT FOUNDATION
		H/h <sub>1</sub>	D	W	lm	lm / W	W	lm	lm / W	
172-0024-000192	BOLUX LO 1,2	120/113	13,3	6,5	1240	190	8,5	1050	124	FBO-50/7,5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.