

## Garden Lamp BOVER K 0,6 COB



## **PRODUCT DESCRIPTION**

Modern LED lantern with a square cross-section. Its column is made of aluminium profiles joined together. In the upper part, the accessories chamber is closed by a plate with a sealed LED module (with the lens) mounted from the outside and a heat-sink - from the inside. Optionally, an IP 54 plug socket can be mounted.

HEIGHT: 0,6 m


## **TECHNICAL SPECIFICATIONS**

| Voltage                | 230 V                              |  |  |  |  |  |
|------------------------|------------------------------------|--|--|--|--|--|
| Source power / fixture | Recommended: Integrated 8 W/960 lm |  |  |  |  |  |
| Lifetime               | 70.000 h LB 80/20                  |  |  |  |  |  |
| Optics                 | S                                  |  |  |  |  |  |
| Ambient temperature    | -30 ÷ +45                          |  |  |  |  |  |
| Light color            | 4000 3000 *                        |  |  |  |  |  |
| Ingress Protection     | IP65                               |  |  |  |  |  |
| Protection class       |                                    |  |  |  |  |  |
| CE                     | Yes                                |  |  |  |  |  |
| *choice                |                                    |  |  |  |  |  |
| MECHANICAL DATA        |                                    |  |  |  |  |  |
| Foundation             | FBO-35/9                           |  |  |  |  |  |
| Column/body material   | Aluminium                          |  |  |  |  |  |
| Lightshade             | РММА                               |  |  |  |  |  |
| Metal color            | White 9003                         |  |  |  |  |  |
|                        | Grey 7043                          |  |  |  |  |  |
|                        | Graphite 7016                      |  |  |  |  |  |
|                        | Black 9005                         |  |  |  |  |  |
|                        | RAL*                               |  |  |  |  |  |
| ON ORDER               |                                    |  |  |  |  |  |
| 2700°K 200 mA          | -Č-                                |  |  |  |  |  |

 $\odot$ 

5000°K 1050 mA





OPTICS



## DETAILED DESCRIPTION

| INDEX        | NAZWA<br>NAME      | WYMIARY / DIN | DIMENSIONS (cm) ŹRÓDŁO ŚWIATŁA |     | WIATŁA / SOURCI | ATŁA / SOURCE OF LIGHT |   | OPRAWA / FIXTURE |        |            |
|--------------|--------------------|---------------|--------------------------------|-----|-----------------|------------------------|---|------------------|--------|------------|
|              |                    | H/h,/h₂       | S                              | W   | Im              | lm / W                 | W | lm               | lm / W | FOUNDATION |
| 172-00000155 | BOVER K LO 0,6 COB | 60/55         | 15x15                          | 6,5 | 1200            | 180                    | 8 | 960              | 120    | FBO-35/9   |

DIM

\*\* on special order

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.