


Garden Lamp BOVER K 1,2 COB



OPTICS "S"



DETAILED DESCRIPTION

IP 65	CLASS /	C€	ENERGY D	IK 08	4000°K 3000°K	CRI ≥80

PRODUCT DESCRIPTION

Modern LED lantern with a square cross-section. Its column is made of aluminium profiles joined together. In the upper part, the accessories chamber is closed by a plate with a sealed LED module (with the lens) mounted from the outside and a heat-sink - from the inside. Optionally, an IP 54 plug socket can be mounted.

HEIGHT: 1,2 m


TECHNICAL SPECIFICATIONS

Voltage	230 V				
Source power / fixture	Recommended: Integrated 8 W/960 lm				
Lifetime	70.000 h LB 80/20				
Optics	S				
Ambient temperature	-30 ÷ +45				
Light color	4000 3000 *				
Ingress Protection	IP65				
Protection class	I II *				
CE	Yes				
*choice					

MECHANICAL DATA

Foundation	FBO-50/9				
Column/body material	Aluminium				
Lightshade	PMMA				
Metal color		White 9003			
		Grey 7043			
		Graphite 7016			
		Black 9005			
	RAL*				

ON ORDER



^{**}on special order

INDEX	NAZWA NAME	WYMIARY / DIMENSIONS (cm)		ŹRÓDŁO ŚWIATŁA / SOURCE OF LIGHT			OPRAWA / FIXTURE			FUNDAMENT
INDEX		H/h,/h₂	S	W	Im	Im / W	W	lm	Im / W	FOUNDATION
172-00000084	BOVER K LO 1,2 COB	120/115	15x15	6,5	1200	180	8	960	120	FBO-50/9

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.

