


Fixture **ESTELA 72**







OPTICS



DETAILED DESCRIPTION

















PRODUCT DESCRIPTION

A family of modern fixtures adapted for mounting at the post or boom (fi 60 mm) with their height within 6-8 m. Body made of pressed aluminum casting forms an electrical equipment chamber and provides the grounds for mounting an adjustable bracket and mounting panel, energy-saving and sealed LED modules. The variety of light distribution and possible configurations allows the designer to choose a variant which gives spectacular effects in line with the customer's expectations.

TECHNICAL SPECIFICATIONS

Voltage	230 V
Source power / fixture	Recommended: Integrated 72 W/90 W
Lifetime	70.000 h LB 80/20
Optics	S AS ASP ASW
Ambient temperature	-30 ÷ +45
Light color	4 000 *
Ingress Protection	IP65
Protection class	I II *
CE	Yes

*choice

MECHANICAL DATA

Foundation -

Column/body material Aluminium

Lampshade

Metal color

White 9003
Grey 7043
Graphite 7016
Black 9005
RAL*

ON ORDER

DIM	-	300 mA _ 1050 mA	10kV	(p

^{**}on special order

INDEX	NAME	DIMENSIONS [cm]	SOURCE OF LIGHT		FIXTURE			WIND	WEIGHT	
		L/B/H	W	lm	Im / W	W	lm	lm/W	m²	kg
195-1111-000032	ESTELA 72	40/40/9	72	11100	154	90	10500	117	0,06	6,5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.