


Fixture **GEDANIA 32**







OPTICS



DETAILED DESCRIPTION

















PRODUCT DESCRIPTION

Universal classic fixture for mounting directly at posts (ř60 mm) or in armsystems at a height of 3-5 m. Aluminum body forms a sealed chamber (closed with a plate) with a sealed LED module (with the lens) from the outside. The chamber is seated on profiles connected to its lower rosette, which also serves as a mounting for the fixture on a post. Lamp-shade made of polycarbonate being resistant to UV radiation.

TECHNICAL SPECIFICATIONS

Voltage	230 V
Source power / fixture	Recommended: Integrated 32 W/36 W
Lifetime	70.000 h LB 80/20
Optics	S AS ASP ASW
Ambient temperature	-30 +35
Light color	4000 3000 *
Ingress Protection	IP65
Protection class	I II *
CE	Yes

^{*}choice

MECHANICAL DATA

Foundation

Column/body material Aluminium Lampshade **PMMA**

Metal color




Grey 7043

Graphite 7016

Black 9005

ON ORDER



^{**}on special order

INDEX	NAZWA NAME	DIMENSIONS [cm]	SOURCE OF LIGHT		FIXTURE			WIND	WEIGHT	
		L/B/H	W	lm	lm / W	W	lm	lm / W	m²	kg
195-1111-000030	GEDANIA 32	35/35/70	32	3900	154	36	3400	92	0,11	5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.

