




## Garden Lamp KALUX 0,6



### PRODUCT DESCRIPTION

Square aluminum column with a characteristic oblique undercut allows to fix LED light source at an angle that allows to illuminate paths or create other accents in the area.

Designed for: illumination of parks, areas around buildings, pedestrian and bicycle paths, gardens and public spaces.  
HEIGHT: 0,6 m

### TECHNICAL SPECIFICATIONS


Voltage	230 V
Source power / fixture	Recommended: Integrated 8,5 W/1050 lm
Lifetime	70.000 h LB 80/20
Ambient temperature	-30 ÷ +45
Light color	<input type="checkbox"/> 4000 <input type="checkbox"/> 3000 *
Ingress Protection	<b>IP65</b>
Protection class	<input type="checkbox"/> I <input type="checkbox"/> II *
CE	Yes

\* choice

### MECHANICAL DATA

Foundation	FBO-35/7,5
Column/body material	Aluminium
Lampshade	-
Metal color	<input type="checkbox"/> White 9003 <input type="checkbox"/> Grey 7043 <input type="checkbox"/> Graphite 7016 <input type="checkbox"/> Black 9005 <input type="checkbox"/> <b>RAL*</b>

### ON ORDER



\*\* on special order

### DETAILED DESCRIPTION

INDEX	NAZWA NAME	WYMIARY / DIMENSIONS (cm)		ŹRÓDŁO ŚWIATEŁA / SOURCE OF LIGHT			OPRAWA / FIXTURE			FUNDAMENT FOUNDATION
		H/h <sub>1</sub>	S	W	lm	lm / W	W	lm	lm / W	
172-0024-000195	KALUX LO 0,6	60/53/-	12x12	6,5	1240	190	8,5	1050	124	FBO-35/7,5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.