
≥80

Fixture TUBUS A/G







OPTICS "S"

DETAILED DESCRIPTION




PRODUCT DESCRIPTION

Universal fixture mounted on a wall or lantern. Adjustable angle of light source inclination. A wide range of options and characteristics of light sources (24-60 degrees), depending on the project, makes it possible to provide the desired effects. Body made of aluminum coated with poliester paints in any colour selected from the RAL catalogue, weatherproof. Lampshade made of tempered glass. Reflector made of polished and anodised aluminum.


TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS				
Voltage	230 V			
Source power / fixture	Recommended: Integrated 36 W/40 W			
Lifetime	70.000 h LB 80/20			
Optics	S			
Ambient temperature	-30 ÷ +45			
Light color	4000 3000 *			
Ingress Protection	IP65			
Protection class	I II *			
CE	Yes			
*choice				
MECHANICAL DATA				
Foundation	-			

Aluminium



ON ORDER



^{**}on special order

Column/body material

	INDEX	NAME	DIMENSIONS [cm]	SOURCE OF LIGHT		FIXTURE			WIND	WEIGHT	
			L/B/H	W	lm	Im / W	W	lm	Im / W	m²	kg
	195-1111-000104	TUBUS A/G	43/18/20	36	5760	159	40	3320	81	-	5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.

