






## Fixture TUBUS B



### OPTICS



„S”

### DETAILED DESCRIPTION

INDEX	NAME	DIMENSIONS [cm]	SOURCE OF LIGHT			FIXTURE			WIND	WEIGHT
		L/B/H	W	lm	lm / W	W	lm	lm / W	m <sup>2</sup>	kg
195-1111-000106	TUBUS B	24/13/30	23,5	4100	173	26	2100	81	-	5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.



### PRODUCT DESCRIPTION

Universal fixture mounted on a wall or lantern. Adjustable angle of light source inclination. A wide range of options and characteristics of light sources (24-60 degrees), depending on the project, makes it possible to provide the desired effects. Body made of aluminum coated with polyester paints in any colour selected from the RAL catalogue, weatherproof. Lampshade made of tempered glass. Reflector made of polished and anodised aluminum.

### TECHNICAL SPECIFICATIONS


Voltage	230 V
Source power / fixture	Recommended: Integrated 36 W/40 W
Lifetime	70.000 h LB 80/20
Optics	<b>S</b>
Ambient temperature	-30 ÷ +45
Light color	4000 3000*
Ingress Protection	<b>IP65</b>
Protection class	<b>I II</b> *
CE	Yes

\* choice

### MECHANICAL DATA

Foundation	-
Column/body material	Aluminium
Lampshade	Glass
Metal color	<div style="display: flex; align-items: center;"> <div style="width: 20px; height: 20px; background-color: #f0f0f0; margin-right: 5px;"></div> <span>White 9003</span> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 20px; background-color: #808080; margin-right: 5px;"></div> <span>Grey 7043</span> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 20px; background-color: #404040; margin-right: 5px;"></div> <span>Graphite 7016</span> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 20px; background-color: #202020; margin-right: 5px;"></div> <span>Black 9005</span> </div>
	<b>RAL*</b>

### ON ORDER



\*\* on special order