



Fixture ARIA BIS 25 COB

OPTICS


„S”


PRODUCT DESCRIPTION

Classic fixture adapted for mounting directly at a post with 60mm diameter or in arm-system - Aria, Aria Bis at a height of 3-4 m, Aria Plus at a height of 5-6m. Aluminum body forms a sealed chamber for fittings closed with a plate and a sealed tight LED module (with the lens) attached to it at the lampshade's side. The chamber is seated on shaped profiles connected to its lower rosette, which serves as a mounting for the fixture on a post.


TECHNICAL SPECIFICATIONS

Voltage	230 V	
Source power / fixture	Recommended: Integrated 23,5 W/26 W	
Lifetime	70.000 h LB 80/20	
Optics	<input checked="" type="checkbox"/> S	
Ambient temperature	-30 ÷ +45	
Light color	<input checked="" type="checkbox"/> 4000	<input type="checkbox"/> 3000 *
Ingress Protection	IP66	
Protection class	<input checked="" type="checkbox"/> I	<input type="checkbox"/> II *
CE	Tak	

*choice

MECHANICAL DATA

Foundation	-
Fixture material	Aluminium
Lampshade	-
Metal color	 <input type="checkbox"/> RAL*

ON ORDER


**on special order

DETAILED DESCRIPTION

INDEX	NAME	DIMENSIONS [cm]	LIGHT SOURCE			Fixture			WIND	WEIGHT
		L/B/H	W	lm	lm / W	W	lm	lm / W		
195-1111-000087	ARIA BIS 25 COB	38/38/62	23,5	4460	190	26	3780	140	0,06	3,5

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.

