






Fixture BELL M 2 x 24 AS



OPTICS



„AS”

IP 66	CLASS I/II	CE	ENERGY C/D	IK 09	4000°K 3000K	CRI ≥80
----------	---------------	----	---------------	----------	-----------------	------------

PRODUCT DESCRIPTION

Classic fixture adapted to be mounted on a boom (r60 mm) at a height of 4-7 m. Aluminum body forms a sealed chamber (closed with a plate) with a sealed LED module (with the lens) mounted from the lamp-shade's side and a heat-sink and power supply unit - from the inside. The chamber is connected to the upper rosette, which - apart from its decorative function, also serves as a mounting bracket. Lamp-shade made of polycarbonate being resistant to UV radiation. Light source: LED panel with a system of lenses and reflector forming any required shape of light.

TECHNICAL SPECIFICATIONS

Voltage	230 V
Source power / fixture	Recommended: Integrated 48 W/55 W
Lifetime	70.000 h LB 80/20
Optics	AS
Ambient Temperature	-30 ÷ +45
Light color	4000 <input checked="" type="checkbox"/> 3000 <input type="checkbox"/> *
Ingress protection	IP66
Protection class	I <input type="checkbox"/> II <input checked="" type="checkbox"/> *
CE	Yes

*choice

MECHANICAL DATA

Foundation	-
Column/body material	Aluminium
Lampshade	PMMA
Metal color	White 9003 Grey 7043 Graphite 7016 Black 9005 RAL*

ON ORDER

DIM	2700°K - 5000°K	300 mA - 1050 mA	10kV	
-----	-----------------------	------------------------	------	--

**on special order

DETAILED DESCRIPTION

INDEX	NAME	DIMENSIONS [cm]	LIGHT SOURCE			Fixture			WIND	WEIGHT
		L/B/H	W	lm	lm / W	W	lm	lm / W		
195-1111-000079	BELL M 2x24 AS	56/56/44	48	8784	183	55	7200	130	0,12	6

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.